

Specifications

Model			BX2350		
Engine					
Type			Liquid-cooled, 3-cylinder diesel		
Model			Kubota D902		
max. Engine power, SAE		kW (PS)	18,5 (25,2)		
Engine power, ECE-R24		kW	15,2		
Displacement		cm³	898		
Fuel tank capacity		l	25		
Drive train					
Transmission			HST, High-Low gear shift (2 forward / reverse)		
Drive method			2WD and 4WD selection		
Brakes			Wet disc		
PTO			Live independent, wet hydraulic clutch		
Rear			STD (540rpm)		
Mid			STD (2500rpm)		
Hydraulics					
Pump output		l/min.	23,5		
3-point hitch			Category I		
Lift capacity @ 24" behind pin		kg	550		
Steering			Hydrostatic Power Steering		
Tyre size					
	Front	Turf/Bar/Industrial	18 × 8.5–10 / 18 × 8.5–10 / 18 × 8.5–10		
	Rear	Turf/Bar/Industrial	26 × 12–12 / 26 × 12–12 / 26 × 12–12		
Travelling speeds at rated engine rpm (Turf)		Forward km/h	0–15.0		
		Reverse km/h	0–10.0		
Dimensions					
Length with 3-point hitch		mm	2554		
Width (w/ turf tyre)		mm	1145		
Height with ROPS		mm	2165		
Wheelbase		mm	1400		
Ground clearance (front axle)		mm	175		
Tread		Front mm	910		
		Rear mm	820		
Turning radius (w/o brake)		m	2.3		
Tractor weight		kg	625		

Loader Specifications

Model		LA243
		BX2350
Max. lift height (to bucket pivot pin)	mm	1810
Dumping clearance	mm	1330
Dumping reach at max. lift height	mm	735
Max. dump angle	degrees	45
Reach with bucket on ground	mm	1390
Bucket rollback angle	degrees	29
Digging depth	mm	120
Overall height in carrying position	mm	990
Bucket width	mm	1219
Lift capacity (500mm fwd., max. height)	kg	235
Breakout Force (500mm fwd.)	N	4410
Raising time to full height w/o load	seconds	3.5
Lowering time w/o load	seconds	2.7
Bucket rollback time	seconds	2.4
Bucket dumping time	seconds	1.7

Rated flow	l/min	14
Relief valve PSI	psi (bar)	1778 (125)
Lift cylinder bore diameter	mm	40
Tilt cylinder bore diameter	mm	65
Bucket capacity (struck)	m³	0.14

Mid-Mount Mower Specifications

Model	RCK48-23BX		RCK54-23BX	RCK60B-23BX
Type	Side discharge		Side discharge	
Number of blades	3			
Mounting method	Suspended-Linkage			Self Balance
Cutting width mm	1224		1372	1524
Cutting height mm	25–102			
Adjustment of cutting height	Dial gauge			
Weight kg	75	95		115

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty and safety information.

©2006 Kubota Corporation



KUBOTA (DEUTSCHLAND) GmbH

Senefelder Straße 3-5, 63110 Rodgau/Nieder-Roden
Telefon 06106/873-0 Telefax 06106/873-197 E-mail info@kubota.de

www.kubota.de