

VALPADANA

VP 9000 **IS**

VP 9000 **AR**



ORIGINAL
PASSION



VP 9000

9095
IS
AR

90105
IS
AR

Engine		(TIER 3)	(TIER 3)
constructor		FPT	FPT
direct injection		mechanical	mechanical
model		F5A	F5A
max. power (ISO rating)	HP/kW	88 / 65	95 / 70
rated speed	rpm	2300	2300
max. torque	Nm	350	390
max. torque speed	rpm	1300	1250
displacement	cm ³	3200	3200
cylinders / valves		4Turbo / 8	4Turbo / 8
water cooling		STD	STD
fuel tank capacity	litres	60	60
Reverse shuttle			
control		mechanical	
wet disc clutch		STD	
Transmission			
standard gearbox 16FWD + 16REV		STD	
max. speed 40 km/h		STD	
Power take-off			
control		electrohydraulic	
2 speeds 540/750 rpm		STD	
2 speeds 540/1000 rpm		OPT	
ground speed PTO		STD	
Front axle			
four-wheel drive		electrohydraulic engagement	
max. oscillation angle		± 15 degrees	
electrohydraulic differential locks		STD	
Brakes			
control		hydraulic	
rear wet disc brakes		STD	
front wet disc brakes		STD	
Power lift / Hydraulic system			
rise/lower/float control (STD)		draft and position control (OPT)	
electropneumatic suspension for implements		OPT (only IS)	
lift capacity		kg 2300	
hydraulic pump flow (lift + steering system)		l/min 50 + 31	
standard three-point hitch with quick couplings		2 ^a cat	
2-way adjust. three-point hitch with quick couplings		OPT	
no. 2 rear remote valves (1DE + 1DE Float)		STD	
no. 4 rear remote valves (2DE + 2DE Float)		OPT	
free return		STD	
joystick for proportional control of hydr. system		OPT	
Driving position			
platform suspended on silent-blocks		STD	
automatic reverse drive system		OPT	
sprung seat		STD	
Cab			
enclosed cab heated		OPT	
air conditioning		OPT	
Weights (in running order without driver)			
total	kg	2360(IS) - 2200(AR)	
Dimensions			
overhang	mm	1260	
wheelbase	mm	1495	
overall length	mm	3735	
ground clearance	min/max mm	310 / 295	
height to steering wheel	mm	1265	
height to ROPS min/max	min/max mm	2455 / 2425	
track front / rear	min/max mm	1106/1490(IS) - 892/1198(AR)	
width front / rear	min/max mm	1393/1750(IS) - 1179/1513(AR)	

key: STD = standard; OPT = option; – = not available

Cod. 6508854M1 10/2013  I.P.

All data and illustrations provided in this brochure are for information purposes only and can be changed without notice.